



Defoamer

Applications: Additive with strong foam-killing effect. For extraction cleaning or shampooing.

A product specifically for defoaming the dirt-water in the tank of the extraction machine or wet-vacuum. With its high silicone content, Defoamer is extremely effective.

One capful Defoamer undiluted into the dirt-water tank prior to use. This procedure should be repeated after each draining of said tank.



Standard Specifications:

Structure at 25°C: liquid
pH at 20°C: 8.5 - 9.5 as a concentrate
Density: 0.975 - 0.995 g/cm³

Shelf-Life: 2 years after first opening.

Storage: Frost free. Closed properly. Dry.

Contents (acc. to 648/2004/EG): None.

Other contents: Silicone emulsion and water.

Biological Degradability: This product fulfills the criteria stated in the EU directive EC 648/2004 concerning detergents.

Article No. 17005

Packaging: Box of 4 x 5 L.

Labelling according to Regulation (EU) No. 1272/2008:

None.

Classification according to ADR/RID:

This product is no hazardous material according to transport regulations.



Version: 06.04.2016

For samples, technical advice and further information please contact::
CEBE Reinigungschemie GmbH • Ruhrstrasse 47 • 22761 Hamburg • Germany
Fon +49(0)40.851 82 - 0 • Fax +49(0)40.851 82 - 29 • Email: info@cebechem.com • www.cebechem.com

These specifications are according to our current knowledge: they are meant to inform about our products and possibilities for their use. No liability may be inferred from this information.